

TECHNICAL DATA	LB1	LF1	LB2	LF2
Drilling capacity in mild steel	18 mm	18 mm	23 mm	23 mm
Motor	0.45kW 1 or 3 phase	0.45kW 1 or 3 phase	0.45/0.75kW (2 speed) 3 phase	0.45/0.75kW (2 speed) 3 phase
Spindle	2 MT	2 MT	2 MT	2 MT
Drive	Belt, stepped pulleys	Belt, stepped pulleys	Belt, stepped pulleys	Belt, stepped pulleys
Spindle speeds rpm 50Hz	400 - 700 - 1200 - 2100 - 3600	400 - 700 - 1200 - 2100 - 3600	200 - 350 - 400 - 600 - 700 - 1050 - 1200 - 1800 - 2100 - 3600	200 - 350 - 400 - 600 - 700 - 1050 - 1200 - 1800 - 2100 - 3600
Spindle travel	75 mm	75 mm	75 mm	75 mm
Throat depth	185 mm	185 mm	185 mm	185 mm
Column diameter	70 mm	70 mm	70 mm	70 mm
Table - overall	300 x 390mm	300 x 390mm	300 x 390mm	300 x 390mm
Table - working surface	240 x 290mm	240 x 290mm	240 x 290mm	240 x 290mm
Base - overall	240 x 360mm	357 x 523mm	240 x 360mm	357 x 523mm
Base - working surface	n/a	n/a	n/a	n/a
Max distance spindle to table	330mm	740mm	330mm	740mm
Max distance spindle to base	n/a	n/a	n/a	n/a
Overall height	865mm	1710mm	865mm	1710mm
Overall width	280mm	280mm	280mm	280mm
Overall depth	600mm	600mm	600mm	600mm
Approx nett weight	77 kg	133 kg	84 kg	140 kg